

Total Stations

DTM-322

- Legendary Nikon optics
- Fast, accurate EDM
- Convenient and long-lasting rechargeable AA batteries
- Easy-to-use keypad
- Rugged and lightweight
- Linear focusing mechanism



Nikon introduces the DTM-322 Total Station that delivers an economic, versatile, and easy-to-use platform to make sure you get the job done right.

Nikon's legendary optics effectively allow in more light to give you brighter, clearer images. You'll see the difference when you look through a Nikon Total Station even in the low-visibility conditions typical in the field. You'll see much more detail and much less distortion, especially over longer distances. Better optics help you aim more precisely, and they're much easier on your eyes – something you'll really appreciate on long workdays.

The Nikon DTM-322 Total Station is among the fastest total stations in its class, so you can move quickly through your routines and spend less time in the field. The DTM-322 is rugged and lightweight – at 5 kg (11 lb) including the battery.

Using rechargeable, or off-the-shelf AA batteries, the DTM-322 is designed to consume low power and provide the longest possible time in the field.

The Nikon DTM-322 is built tough for all occasions.

SPECIFICATIONS	DTM-322	
DISTANCE MEASUREMENT		
Range with Nikon specified prism	5 m to 100 m (16.4 ft to 328 ft)	
Good conditions (No haze, visibility over 40' (12.5 miles))	2,300 m (7,540 ft)	
With reflector sheet (5' x 5 cm)		
With single prism 6.25 cm (2.5 in)		
Normal conditions (Only haze, visibility approx. 20 km (12.4 miles))	5 m to 100 m (16.4 ft to 328 ft)	
With reflector sheet (5' x 5 cm)	2,000 m (6,560 ft)	
With single prism 6.25 cm (2.5 in)		
Accuracy (Frisar/Precise mode) ¹	±(3+2 ppm × D) mm	
Measuring interval ²	Precise mode	Normal mode
Precise mode	1.6 sec	1.0 sec
Least count (Precise mode/Normal mode)	1 mm (0.002 ft)	10 mm (0.02 ft)
ANGLE MEASUREMENT		
Dillo (18723 accuracy (horizontal and vertical))	5"/1.5 mgon	
Circle diameter	88 mm (3.46 in)	
Horizontal/vertical angle	Single	
Minimum increment	Degree: 1/5/10"; Gon: 0.2/1/2 mgon; MIL6400: 0.005/0.02/0.05 mil	
TELESCOPE		
Magnification	33x (21x/41x with optional eyepieces)	
Minimum focusing distance	1.5 m (4.92 ft)	
TILT SENSOR – Type	Single-axis	
COMMUNICATIONS – Ports	1 x serial (RS-232C)	
POWER		
Clip-on rechargeable battery system	4x AA Ni-MH Battery	
Operating time ³	approx. 15 hours (continuous distance/angle measurement every 30 s)	
GENERAL SPECIFICATIONS		
Level vial – Sensitivity of Plate level vial	30"/2 mm	
Sensitivity of Circular level vial	10"/2 mm	
Optical plumbline		
Magnification	3x	
Focusing range	0.5 m (1.6 ft) to ∞	
Display	Single side, graphic LCD (128 × 64 pixel)	
Point memory	10,000 records	
Dimensions (H × W × D)	168 mm × 173 mm × 335 mm (6.6 in × 6.8 in × 13.2 in)	
Weight		
Askin unit (without battery)	4.8 kg (10.6 lb)	
Battery / Carry case	0.2 kg (0.4 lb) / 2.4 kg (5.3 lb)	
ENVIRONMENTAL		
Ambient temperature range	-20 °C to +50 °C (-4 °F to +122 °F)	
Atmospheric correction		
Temperature range	-40 °C to +55 °C (-40 °F to +131 °F)	
Barometric pressure	400 mmHg to 999 mmHg / 533 hPa to 1,332 hPa / 15.8 inHg to 39.3 inHg	
Dust and water protection	IP55	
CERTIFICATION	Class B Part 15 FCC certification, CE Mark approval, C-Tick	

1 ±(3+3 ppm × D) mm -20 °C to -10 °C, +40 °C to +50 °C (-4 °F to +14 °F, +104 °F to +122 °F)

2 Measuring time may vary depending on measuring distance and conditions.

3 Battery life specification at 25 °C (77 °F)

INDOSURTA GROUP
PT. ALAT UKUR INDOSURTA
 Jl. Bangka Blok N3 No.21 NUSALOKA
 BSD CITY SERPONG
 TANGERANG
 Telp : 021-71277841 / 021-71690885-886
 Fax : 021-71690896
 www.indosurta.com
 SOKKIA - TOPCON - NIKON